



# EV-CHARGING SYSTEMS

GREEN MOBILITY



RAPID CHARGING



USER-FRIENDLY



WEB ACCESS



# FAST-CHARGER

Alternating current (AC) charger



BASIC

SMART

CHARGING CAPACITY

<b>Full support of all European AC charging standards</b>	✓	✓
<b>Fast and easy installation</b>	✓	✓
<b>Charging connection types</b> <ul style="list-style-type: none"> <li>• 1 piece of (AC) Type2 connector with 5 m spiral-cable</li> <li>• 1 piece of (AC) Type2 socket</li> </ul>	✓	✓
<b>Installation options</b> <ul style="list-style-type: none"> <li>• Floor-standing</li> <li>• Wall-mounted</li> <li>• Pylon-mounted</li> </ul>	✓	✓
<b>SMART communication functions</b> <ul style="list-style-type: none"> <li>• Web-based access and monitoring for operators</li> <li>• RFID (magnetic card) identification</li> <li>• Measurement of real electric consumption</li> <li>• SMS-based charging management (activation)</li> </ul>	—	✓

1-phase		3-phase	
230 V		400 V	
16 A	32 A	16 A	32 A
3,7 kW	7,4 kW	11 kW	22 kW



For more information about charging times related to specific vehicles visit:

[www.evopro.hu/eng/page/charging\\_duration](http://www.evopro.hu/eng/page/charging_duration)



# RAPID-CHARGER

AC/DC rapid charging

## CHARGING CAPACITY

AC		DC	
1-phase	3-phase	3-phase	
230 V	400 V	50-500 V	
16 A    32 A	16 A    32 A	max 125 A	
3,7 kW   7,4 kW	11 kW   22 kW	max 50 kw	

**Charging to 80% even in less than 30 minutes**

**Integrated AC/DC converter**

**Simultaneous AC & DC charging**

**Charging connection types**

- 1 piece of (DC) CCS cabled connector
- 1 piece of (DC) CHAdeMO cabled connector
- 1 piece of (AC) Type2 cabled connector
- 2 pieces of (AC) Type2 sockets

**Floor-standing installation**

**SMART communication functions**

- Web-based access and monitoring for operators
- RFID (magnetic card) identification
- Measurement of real electric consumption
- SMS-based charging management (activation)



CCS



CHAdeMO



AC



# EVOPRO CHARGING SYSTEMS

Safe and quick charging for electric vehicles

## GENERAL FEATURES

Standard remote monitoring system

Status information on LED display

Safe: continuous monitoring of charging cable

Tamper-proof design for outdoor use, with optional protector bars and anti-graffiti coating

Ergonomic design

Easy access and use also for disabled persons

## CONTACT AND ORDERING INFO



+36 1 279 3970



sales@evopro-group.com



www.evopro-group.com

## PRODUCT ORDER NUMBERS

BASIC  
version

SMART  
version

Fast-charger (AC)	eAC-B01	eAC-S01
Rapid-charger(AC/DC)	—	eDC-S01

INSTALLATION ADAPTERS  
For Fast-charger (AC)

Floor-standing	A1
Pylon-mounted	A2
Wall-mounted	A3